

X-RAY MEASURING APPARATUS AND METHOD

Patent Number: JP2001013094
Publication date: 2001-01-19
Inventor(s): DOSHIYOU AKIHIDE
Applicant(s): RIGAKU CORP
Requested Patent: ☐ JP2001013094
Application Number: JP19990185256 19990630
Priority Number(s):
IPC Classification: G01N23/207
EC Classification:
Equivalents:

Abstract

PROBLEM TO BE SOLVED: To enable the measurement of a sample over a range from the minute region of the sample to the wide region thereof by one X-ray optical system in a case performing measurement, by adjusting the X-ray irradiation field to the sample by using a collimator or the like, and to obtain data of high dissolving power in relation to the whole range from the minute region to the wide region.

SOLUTION: A sample S is irradiated with X-rays in a narrow X-ray irradiation field A by a collimator 1 and X-rays diffracted by the sample S are detected by a storage phosphor 2. When the measuring region B of the sample S is wider than the X-ray irradiation region by the collimator 1, the sample S is moved in parallel to the collimator 1 by an XY parallel moving device 6 to scan and move the X-ray irradiation field A to regulate the measuring region B. Diffracted X-ray data are successively integrated on the stimuable phosphor 2 when the X-ray irradiation field is present at the individual positions in the measuring region B.

Data supplied from the esp@cenet database - I2